



Photovoltaic Solar Module Manufacturer  
ISO 9001:2000

## KORAX SOLAR PHOTOVOLTAIC MODULE KS-20

---

### Category overview

---

Category:	Monocrystalline
Module size (length x width):	638 mm x 286 mm
Area:	0,182 m <sup>2</sup>
Thickness incl. Frame:	39,5 mm
Weight:	1,8 kg

---



### Technical data:

<b>Output classes (Wp):</b>	20
<b>Electrical data at STC<sup>1</sup> standards:</b>	
Tolerance (%):	10
MPP Voltage (V)	17,53
MPP Current (A)	1,15
Open-circuit voltage (V)	21,89
Short-circuit current (A)	1,27
Module efficiency (%)	10,9

### Other parameters:

Cells	36 piece monocrystalline solar cells
Cell dimension	31,25 mm x 31,25 mm
Front	Tempered solar glass, highly transparent
Encapsulation	EVA – cell – EVA
Back	Tough multilayered backsheets Tedlar
Frame:	Anodised aluminium
Connection:	IP65 with built-in bypass diode,
Bypass diodes:	1 pieces

---

**Qualifications and Certificates:** CE, according to EN 61215 ed.2 and EN 61730

---

### YOUR DEALER:

---

1) STANDARD TEST CONDITION: AIR MASS AM 1,5 – IRRADIATION 1000 W/m<sup>2</sup> – CELL TEMP. 25°C